


CURVE INOX A LARGO RAGGIO

CURVE INOX R = 2,5 D



MATERIALE: AISI 304/304L - AISI 316/316L

DN	POLLICI	De	R	SPESSORE
15	1/2"	21,3	45	2
20	3/4"	26,9	57	2
25	1"	33,7	72	2
32	1"1/4	42,4	93	2
40	1"1/2	48,3	108	2
50	2"	60,3	135	2
65	2"1/2	76,1	175	2
80	3"	88,9	205	2
100	4"	114,3	270	2

NORMA: EN10253-3



Possiamo fornire anche curve con raggio di curvatura fino a 10 volte e più diametro minimo 2" - 60,3 in acciaio inox ed in ferro...  
NB.: ARTICOLI SOGGETTI A QUANTITATIVI MINIMI DI FORNITURA



CURVE A MANDRINARE A PAG. 215

FONDI BOMBATI INOX

MATERIALI : AISI 304L - 316L

A RICHIESTA:

- FINO A DN 2000 (con foro centrale)
- A FONDO PIATTO

N.B. : LA QUOTA "H" NON E' IMPEGNATIVA



SPESSORI STANDARD: 2/3 mm.

CERTIFICATI: EN 10204 2.2

FONDI "ISO"

FONDI "METRICI"

FONDI "DIN-SMS"



NORMA: EN 10253-3

DIMENSIONI in mm.				
DN	POLLICI	D	H	S
10	3/8"	17,2	11,5	2
15	1/2"	21,3	10-15	2-3
		25	12-14	1,5-2
20	3/4"	26,9	11-12	2-3
		28	10-12	1,5-2
		30	10-12	1,5-2
25	1"	33,7	12,5-14	2-3
		38	11-15	1,5-2
32	1"1/4	42,4	13-17	2-3
		44,5	13-16	2
40	1"1/2	48,3	17-23	2-3
		50,8	13-19	1,5-2
		52	15	2
50	2"	60,3	20	2-3
		70	21	2

DIMENSIONI in mm.				
DN	POLLICI	D	H	S
65	2"1/2	76,1	27	2-3
		80	23	2
		84	20-23	2
80	3"	88,9	29	2-3
		101,6	27	2-3
		104	20-24	2
100	4"	114,3	32	2-3
		129	34	2
125	5"	139,7	35	2-3
		154	41	2
150	6"	168,3	40	2-3
		204	50	2
200	8"	219,1	50	2-3
		254	55	2
250	10"	273	63	2-3
300	12"	323,9	72	2-3
350	14"	355,6	89	3
400	16"	406,4	107	3-4
450	18"	457,2	120	3-4
500	20"	508	140	3-4
600	24"	609,6	152	3-4